



www.dgaus.com.au



DIESEL GENERATION AUSTRALIA

Richard Manning 0407 919 474 E: Ricard.Manning@dgaus.com.au Hamish Barr 0405 184 462 E: Hamish.Barr@dgaus.com.au

61A Lampton Ave, Derewnt Park, Tasmania. R&B INDUSTRIES PTY LTD

A.B.N:92351287205

DGA 7000- 7 kVA 240V Diesel Generator

Prime Power :	6.0KW / 6.0KVA 240 Volts 25Amps
Standby Power :	7.0KW / 7.0KVA
Phase Voltage :	Single Phase 240 Volt
Frequency :	50 Hertz
Engine :	OEM Single Cylinder 13hp Yanmar Style Diesel
RPM :	3000/min (Clockwise - View From Flywheel)
Cooling Method :	Air Cooled - Volume Air Circulation System for Better Cooling
Oil type & Capacity :	15W/40 - 1.6LT
Alternator :	Brushed with AVR (Low THD <5%, Clean Sinewave Power)
Starter System :	12 volt Electric - Large 45A/H Battery Included
Controller :	Smartgen HGM410 2 Wire / Remote Start Capable Low Oil Protection
Safety Systems :	Battery Isolator* Emergency Stop
Noise Level :	67 dBA at 7 metres
Fuel Tank Capacity :	25 Litres (-/c Fuel Gauge)
Running Time :	20-22 Hours Depending On Load
Fuel Consumption :	1.1 litres/hour (Average)
Chassis Enclosure :	Silenced Cabinet Sound Deadening Weather Resistant External Use
Mine Site Ready Bunding :	Yes
ATS (Mains Failure) :	Easy Connect Plug (ATS Box Optional)
DC Outlets:	12 Volt 8.3 Amps
Single Phase Outlets :	2 x IP66 15 Amp 1 x IP66 32 Amp
Three Phase Outlets :	No
Hardwire Terminals :	No
ELCB :	IP66 Enclosed Earth Leakage Circuit Breaker / RCBO
Weight :	260 kg
Dimensions :	106 L x 69 W x 95 H cm

